



VESSELS PARTICULARS	
LENGTH OVERALL	142 FT
BEAM HULL	29 FT
MAX BEAM	31 FT
DEPTH	14 FT
LIGHT DRAFT	5 FT 6 IN
MAX DRAFT	8 FT 6 IN
AIR DRAFT	42 FT
LIGHTSHIP DISPLACEMENT	125.2 LT
MAX DISPLACEMENT	380 LT
PERFORMANCE	
SPEED LIGHT BOAT	22 KTS @ 155 GPH
SPEED LOADED	17 KTS @ 190 GPH
DECK CARGO	
CLEAR DECK	87 FT X 25 FT
TONNAGE	225 LT (AS PER STABILITY LETTER)
CAPACITIES	
FUEL	19,796 US GAL
RIG WATER (PORTABLE)	35,682 US GAL
SHIPS POTABLE	778 US GAL
LUBE OIL TANK	160 US GAL
DIRTY OIL/BILAGE WATER	1,146 US GAL
GREY WATER	2,244 US GAL
SEWAGE HOLDING WATER	988 US GAL
GREY WATER HOLDING TANK	539 US GAL
ACCOMMODATIONS	
PASSENGERS	32 (SEATED)
STAFF ROOMS	4 - 2 MEN
	17 TOTAL BUNKS
HEADS	2
GALLEY SEATING	8
AIR CONDITIONING/HEATING	2 UNITS
WALK IN COOLER	196 CUBIC FT
WALK IN FREEZER	N/V

ELECTRONICS	
VHF	3
SSB	1 FURUND
RADARS	2 FURUND
GPS	1 FURUND
COMPASS	1 MAGNETIC
AIS SYSTEM	1 FURUND
NAVTEX	1
DEPTH SOUNDER	1 FURUND
TRANSFER RATES	
FUEL	240 GPM @ 150 FT
RIG WATER	240 GPM @ 150 FT
MACHINERY	
TOTAL HORSEPOWER	4125 BHP
MAIN ENGINES	(5) CAT 3412 @ 825 HP
GEARS	(5) 2.5:1 TO 1:2F 1900
PROPELLERS	40 X 40 4- BLADE
GENERATORS	(2) 90 KW 6068 JOHN DEERE
FIRE MONITORS	1000 GPM
DOCUMENTATION-CERTIFICATION	
YEAR BUILT/REFITTED	2001
BUILDER	C&G BOATWORKS, INC
TONNAGE	89 - GRT EO - NRT
HOME PORT	LAGOS
FLAG	NIGERIA
ABS CERTS	INT LOADLINE
USCG CERTS	SUBCHAPTER T OCEANS 200 NM
ZERO DISCHARGE	ZERO DISCHARGE CAPABLE
ADDITIONAL EQUIPMENT	
DAVIT RETRIEVAL SYSTEM	1 STBD SIDE
ANCHORS(S)	2 @ 150 LBS

Equipped with Ballistic Protection

Entire wheelhouse is protected up to 1.2m waist height using composite light weight material. Threat level protection up to NIJ level III + which is against 7.62 x 39MSC (AK47).